

# BZB-2



## Maximum Performance with Economic Price

BZB-2 is versatile in capability, the excellence of well design for large label roll has been granted patent rights in Taiwan, USA and China. BZB-2 is simple to use and install for home and office use.

- Line mode printing in direct thermal mode
- 203dpi of print resolution
- Text, barcodes, and graphics printing
- Free BZB label design software and Windows driver
- Compatible with Windows 3.1/95/98
- Adjustable print speed and darkness from the software
- Internal label roll of 4" OD capacity expandable to 10" external OD capacity
- Ideal for address/mailling labels, price tags, and file records etc.
- Easy connection to ODBC database.



**GODEX**



ISO 9001:2000 CERTIFIED



Symbol of Excellence

## BZB-2 Specifications

<b>Model</b>	<b>BZB-2</b>
Resolution	203 dpi (8 dot/mm)
Print Mode	Line Mode Direct Thermal
CPU	16 Bit
Sensor Location	Center aligned
Sensor Type	Reflective, Transmissive
Sensor Detection	Label gap and black mark sensing
Print Speed	50.8mm/sec (2ips)
Print Length	Max. 203mm (8")
Print Width	Max. 56mm (2.20")
Media	Type:Roll-feed, Die-cut, plain paper, and Fan-fold Core:1" core Width:61mm Thickness:0.06mm~0.15mm
Software	Application: BZB label design software Windows Driver:Microsoft Windows 95, 98, Me, NT, and 2000
Fonts	Windows fonts through software
Barcode	Code 39, Code 93, Code 128, UCC 128, UPC A / E (add on 2 & 5), I 2 of 5, EAN 8 / 13 (add on 2 & 5),Codabar, Post NET, EAN 128, DUN 14, MaxiCode and PDF417
Interface	Centronics Parallel Port
Memory	64KB EPROM and 32KB SRAM
Power	AC 120 V or 230V, DC 15V4A
Environment	Operation:40°F to 104°F (5°C to 40°C) Storage:-40°F to 122°F (-20°C to 50°C)
Humidity	Operation:10~90%, non-condensing. Free air.
Cert. Approval	CE, UL, CSA, FCC Class A
Printer Dimension	Depth:127mm (5") Height:215mm (8.5") Width:144mm (5.5") Weight:1.3 Kg

Specifications subject to change without notice.