

### The First Fanless Intel Atom Thin Client in the World

TK-3880 is based on the Intel Atom platform and the first one fan less thin client in the world. TK-3880 is designed to integrate the newest Intel Atom N270 QS 1.6GHz and 945GSE chipset that is the lowest consumption (20W). TK-3880 breaks the application boundary of traditional application of Intel to go into the thin client. It will go with the Termtek latest Linux image with Ubuntu 7.10 and Win CE image with R2 version to offer your completed integrated thin client solution.

### Dual display screen support: VGA& DVI

TK-3880 have the wider view on your site equipped with the VGA and DVI connector. You have two screens at the same time for your special requirements or Digital Signage application. You don't need to buy two clients to fulfill with your function and save your money.

### Additional slots support: (Option) Wireless LAN, PCI-e, and Smart Card

TK-3880 supports internal USB 2.0 wireless module, and is compatible with IEEE802.11 b/g wireless connection. For users looking for higher security, TK-3880 is even equipped with a smart card slot as an optional function. Either the internal SATA H.D.D kit or the PCI-e(4x) riser card kit can offer more application options

CPU Type	Intel Atom N270 QS
Processor speed	1.6GHz
Chipsets	945GSE+ICH7M
Operating system	Microsoft Windows CE 6.0 Linux Kernel 2.6 Microsoft Windows XPe SP2
Browser	IE 6.0 for CE6.0, IE7.0 for XPe Firefox 3.0 for LX
Compact Flash memory (standard)	256MB for CE6.0 512MB for LX 512MB for XPe (expandable to 4GB for XPe)
RAM (standard)	256MB DDRII(400/533) for CE6.0 512MB DDRII for LX 512MB DDRII for XPe (expandable to 2GB for CE, Linux, XPe)
I/O Ports	1 x VGA video output, 1 x DVI-D video output, 8 x USB 2.0(6x External and 2x Internal), 1 x RJ-45 1 x Line in, 1 x Line out
Standard Option	<ul style="list-style-type: none"> <li>• Metal mounting bracket for VESA</li> <li>• Internal USB 802.11b/g Wireless LAN module</li> <li>• Smart Card Reader Kit</li> <li>• Internal SATA H.D.D Kit/PCI-e(4X) riser card Kit(Either one)</li> </ul>
Manageability software	Remote Management 6.0 SP1
Protocols	MS RDP 5.2, ICA 10.0 for CE6.0 MS RDP 6.0, ICA 10.0 for XPe rdesktop 1.5.0, ICA 10.6 for LX Terminal Emulation (Default for CE/LX and optional for XPe)
Dimensions	251mm(L)x214mm(W)x55mm(H) weight: 1.6 kg only



## TK-3880 CE6.0 R2/LX/XPe

The First Intel Atom Thin Client in the World

TERMTEK COMPUTER CO.,LTD.

<http://www.termtek.com.tw>

## TK-3880 CE6.0 R2/LX/XPe Specification

