

SPECIFICATIONS

8000 series

Pocket-size Mobile Computer



		8000	8001	8061	8071
Wireless Communication	Options	Batch		Bluetooth	Wi-Fi
	Specifications	Infrared		BT Class 1	802.11b/g
	Coverage line of sight	Typically 30 cm / 12 in.		250 m / 820 ft.	350 m / 1148 ft.
Power	Operation battery	2 AAA alkaline	Li-ion 3.7 V 700 mAh		
	Backup battery	Rechargeable lithium 3.0 V, 7.0 mAh			
	Working time laser, one scan per five seconds	100 hours		36 hours	22 hours
	Data retention	30 days			
General Characteristics	CPU	16-bit CMOS, low power consumption			
	Program memory	2MB flash memory			
	Data memory	2MB SRAM			
	Display	LCD 100 x 64 with LED backlight			
	Keypad	21 rubber keys with LED backlight			
	Buzzer	Programmable, 1 KHz to 4 KHz			
	LED	Dual color: red and green			
Dimensions	Size L x W x H	122 x 56 x 23 mm 4.8 x 2.2 x 0.9 in.	122 x 56 x 32 mm 4.8 x 2.2 x 1.25 in.	143 x 57 x 35 mm 5.6 x 2.25 x 1.4 in.	
	Weight laser including battery	123 g / 4.4 oz.	120 g / 4.2 oz.	125 g / 4.4 oz.	166 g / 5.9 oz.
Scanner	Light source	Linear imager: 650 nm red LED / Laser: visible laser diode			
	Scan rate	Linear imager/Laser: 100 scans per second			
	Scan angle	Laser: 47°			
	Reading range	Linear imager: 3 to 29 cm / 1.2 to 11.4 in. Laser: 1 to 45 cm / 0.4 to 1.5 ft. dependent on barcode resolution			
Environmental	Operating temperature	-10°C to 60°C / 14°F to 140°F			
	Storage temperature	-20°C to 70°C / -4°F to 158°F			
	Humidity	Operating: non-condensed 10% to 90% / Storage: 5% to 95%			
	Impact resistance	1.2 meter / 4 ft. drops onto concrete, 5 drops per 6 sides			
	Electrostatic discharge	± 15 kV air discharge, ± 8 kV direct discharge			
	EMC regulation	FCC, CE, and C-Tick approved			FCC, CE, C-Tick, DGT, BSMI, TELEC, MIC
Programming	C, Basic, and Windows-based applications generator				
Accessories	Charging & communication cradle (serial & USB), Modem cradle (56K), Ethernet cradle (10/100 BaseT), Battery gang charger				
Acoustic Coupler 8020/8021 available in US	Data rate/format: 1200, O/E/N, 7/8, 1/2 stop bits Sound frequency: 1.2 KHz ± 5%, 2.2 KHz ± 5% Modulation type: Bell202/FSK				
Warranty	1 year				

ACCESSORIES



Communications Cradle



Charging and Communications Cradle



**56 Kbps Modem
10/100 Mbps Ethernet Cradle**



Battery Gang Charger



©2006 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All trademarks and trade names are those of their respective owners.



HEADQUARTERS
CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec. 2
Taipei, Taiwan 106
Tel +886 2 8647 1166
Fax +886 2 8732 2255
www.cipherlab.com

CipherLab China
Suite 1305, 1065A, Jaojiabang Rd.
Xuhui District, Shanghai,
China 200030
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CipherLab USA
2552 Summit Avenue
Plano, Texas USA 75074
Tel +1 469 241 97799
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab EMEA
Airedale House
Clayton Wood Rise
Leeds, LS16 6RF, UK
Tel +44 113 274 7823
Fax +44 113 274 7822